







- Bright XGA projector 3800 ANSI lumens
- Easy connectivity HDMI, VGA, USB power
- Clear, powerful audio 10W speaker
- Lightweight and portable

Project bright and vibrant presentations effortlessly any time of day. Designed for meeting rooms and classrooms, the X371 boasts amazing colour, long lamp life and energy-saving features for a lower overall cost of ownership.



This projector is easy to connect to with multiple inputs, a built-in speaker and USB power. Perfect for connecting HDMI dongles such as Google Chromecast or a laptop, PC or Blu-ray player for clear projected images with sound. Portable and lightweight projector can be installed or taken on the move for off-site meetings or classes with the optional carry bag (sold separately).

Specifications

Display/image Display technology	DL₽™
Resolution	XGA (1024x768)
Brightness	3,800 lumens
Contrast ratio	25,000:1
Native aspect ratio	4:3
Aspect ratio - compatible	16:9
Keystone correction - vertical	+/-40°
Horizontal scan rate	+/-40 15.38 ~ 91.15Khz
Vertical scan rate	50 ~ 85(120 for 3D)Hz
Uniformity	75%
Screen size	0.71m ~ 7.73m (27.78" ~ 304.4") diagonal
	0.7 IIII ~ 7.73III (27.78 ~ 304.4) diagonal
Lamp info Light source type	Lamp
Lamp watts	203
Lamp life hours (up to)	6000 (Bright), 12000 (Dynamic), 10000 (Eco), 15000 (Eco+)
	0000 (Englit), 12000 (Eynamic), 10000 (Ec0), 13000 (Ec0+)
Optical Throw ratio	1.94:1 ~ 2.16:1
Projection distance (m)	1.94:1 ~ 2.16:1 1m - 12m
Zoom	1.1
Zoom type Food longth (mm)	Manual
Focal length (mm)	21.85 ~ 24
lative offset	115%
Connectivity	
Connections	Inputs 1 x HDMI 1.4a 3D support, 1 x VGA (YPbPr/RGB), 1
	x Composite video, 1 x Audio 3.5mm
	Outputs 1 x VGA, 1 x Audio 3.5mm, 1 x USB-A power 1A
	Control 1 x RS232
ieneral	
loise level (typical)	27dB
loise level (max)	29dB
C compatibility	FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac
D compatibility	NTSC M/J, 3.58MHz, 4.43MHz PAL B/D/G/H/I/M/N, 4,43MHz
	SECAM B/D/G/K/K1/L, 4.25/4.4MHz 480i/p, 576i/p,
D	720p(50/60Hz), 1080i(50/60Hz), 1080p(50/60Hz)
BD compatibility	Side-by-Side:1080i50 / 60, 720p50 / 60 Frame-pack: 1080p24_720p50 / 60 Over-Linder: 1080p24_720p50 / 60
D	1080p24, 720p50 / 60 Over-Under: 1080p24, 720p50 / 60
	Full 3D Sequrity has Kanajastan Look, Decovered protected interface
Security	Security bar, Kensington Lock, Password protected interface
OSD / display languages	25 languages: Arabic, Czech, Danish, Dutch, English, Farsi, Finnish, French, German, Greek, Hungarian, Indonesian, Italian,
	Japanese, Norwegian, Polish, Portuguese, Romanian, Russian,
	Chinese (simplified), Spanish, Swedish, Chinese (traditional),
	Turkish, Vietnamese
Operating conditions	5°C ~ 40°C, Max. Humidity 85%, Max. Altitude 3000m
Remote control	Card style
eaker count	1
Vatts per speaker	10W
n the box	AC power cord
	Remote control
	Battery
	Basic user manual
ptional wireless models	HDCast Pro, QuickCast Bundle, QuickCast starter kit,
1	WHD200
ower	100 0401/ 50 0011-
ower supply	100 ~ 240V, 50 ~ 60Hz
Power consumption (standby)	0.5W
Power consumption (min)	187W
Power consumption (max)	225W
Neight and dimensions	
Dimensions (W x D x H) mm	316 x 244 x 108
	0.50.1.5
Gross weight Net weight	3.58 kg 3.04 kg







Copyright © 2021, Optoma and its logo is a registered trademark of Optoma Corporation. Optoma Europe Ltd is the licensee of the registered trademark. All other product names and company names used herein are for identification purposes only and may be trademarks or registered trademarks of their respective owners. Errors and omissions excepted, all specifications are subject to change without notice. All images are for representation purposes only and may be simulated. 15082021015910