

# GT2200HDR

Compact high brightness Short throw Full HD 4LED projector



- **Bright 3300 lumens for lights on viewing - Full HD 1080p 4LED projector**
- **Eco-friendly design - Low power consumption, energy saving and a long product lifespan**
- **Short throw lens for gaming - 100" image from just over a metre away**
- **Optoma Smart Control App - Providing the ultimate flexibility, this projector's short throw lens is perfect for smaller spaces and combined with Optoma's new SmartApp, allows for quick adjustments to your setup all from your mobile device**



The GT2200HDR is one of Optoma's most compact and hassle-free Full HD projectors to date. Designed for maintenance-free continuous operation, this 3300-lumen projector delivers powerful image performance and provides an easy setup in any space around the home, with a short throw lens and extensive connectivity options in a sleek, compact form factor.

Use Optoma's latest Smart Control App to make quick adjustments to your setup and take advantage of low latency gaming mode for lightning quick response times.

# Specifications

EAN: 5055387669710, Colour: Black

The following specifications are preliminary and subject to change without notice

## Display/image

Display technology	DLP®
Resolution	1080p Full HD (1920x1080)
Brightness	3,300 lumens
Contrast ratio	500,000:1
Native aspect ratio	16:9
Aspect ratio - compatible	4:3,16:9,16:10
Keystone correction - horizontal	+/-30°
Keystone correction - vertical	+/-30°
Displayable colours (millions)	1073.4
Horizontal scan rate	15 ~ 135Khz
Vertical scan rate	24 ~ 120Hz
Uniformity	85%
Screen size	0.76m ~ 7.62m (30" ~ 300") diagonal

## Lamp info

Light source type	4 LED
LASER life	30,000 hours

## Optical

Throw ratio	0.69:1 ~ 0.83:1
Projection distance	0.458m - 5.512m / 18.03" - 217.01"
Zoom	1.2
Zoom type	Manual
Focal length	10.2 ~ 12.24
Native offset	102%

## Connectivity

Connections	<b>Inputs</b> 2 x HDMI 2.0, 1 x VGA, 1 x Audio 3.5mm <b>Outputs</b> 1 x Audio 3.5mm, 1 x USB-A power 1.5A <b>Control</b> 1 x RS232, 1 x RJ45
-------------	--

## General

Noise level (min)	29dB
Noise level (max)	35dB
PC compatibility	FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac
Security	Security bar, Kensington Lock, Password protected interface
OSD / display languages	25 languages: Arabic, Czech, Danish, Dutch, English, Farsi, Finnish, French, German, Greek, Hungarian, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Russian, Chinese (simplified), Spanish, Swedish, Chinese (traditional), Turkish, Vietnamese
24/7 operation	Yes
360° operation	Yes
Operating conditions	0°C ~ 40°C, Max. Humidity 80%, Max. Altitude 10000ft.
Speaker count	1
Watts per speaker	10W
In the box	AC power cord Remote control 2x AAA Batteries Basic user manual

## Power

Power supply	AC 100 ~ 240V, 50 ~ 60Hz
Power consumption (standby)	<0.5W
Power consumption (min)	124W
Power consumption (max)	226W

## Weight and dimensions

Dimensions (W x D x H)	307 x 228 x 125 mm / 12.09" x 8.98" x 4.92"
Gross weight	5 kg / 11.02 lbs
Net weight	3.2 kg / 7.05 lbs