

AXIS T8310 Video Surveillance Control Board

Modular control board for professional camera and video management

AXIS T8310 Video Surveillance Control Board is a modular system with three separate joystick, keypad and jog dial units. AXIS T8311 Video Surveillance Joystick gives responsive and accurate control of all Axis PTZ network cameras. With AXIS T8312 Video Surveillance Keypad the user quickly navigates between workspaces, cameras, views and PTZ presets. AXIS T8313 Video Surveillance Jog Dial is used for navigating through recorded video. The units are easy to install via the USB interface. The modular system allows users to choose a simple solution (joystick only), or a complete solution (all three modules) for both camera and video management.

- > [Modular system](#)
- > [Accurate control of PTZ cameras](#)
- > [Professional design](#)
- > [Easy to install](#)



General specifications — all models

| General | |
|----------------------|--|
| Power | Via USB interface |
| Casing | Polycarbonate ABS |
| Operating conditions | 0 °C to +60 °C (32 °F to 140 °F) Humidity 10–85% RH (non-condensing) |
| Storage conditions | -10 °C to +60 °C (14 °F to 140 °F) |
| Approvals | EN 55032 Class B, EN 55024, EN 61000-6-2, FCC Part 15 Subpart B Class B, RCM AS/NZS CISPR 32 Class B, |
| | ICES-003 Class B, VCCI Class B, EN/IEC/UL 62368-1, KC KN-32 Class B KN 35, EN 60529 IP20 |
| System requirements | Windows 10, Windows 7, Windows XP, Windows Vista, Windows 12 (Server), Windows 8 (Server), USB 2.0 port |
| Compatible products | Axis network video cameras Axis network video encoders |
| Warranty | Axis 3-year warranty, see axis.com/warranty |

AXIS T8311 Video Surveillance Joystick

| Functionality | |
|---------------------------|--|
| | Hall-effect joystick with three axis: X/Y: for pan and tilt, Z: knob for zoom Deflection by square delimiter, ($\pm 15^\circ$) for XY, ($\pm 25^\circ$) for Z 6 hotkeys with customizable function |
| | Width: 182 mm (7.2 in) Depth: 181 mm (7.1 in) |
| General | |
| Connectors | USB Type B |
| Dimensions | Height: 109 mm (4.3 in) |
| Weight | 730 g (1.6 lb) |
| Included accessories | Installation guide, 1 x USB cable 200 cm (78.7 in) for connection to PC |
| Video management software | AXIS Camera Station version 5.17 or higher, video management software from Axis Application Development Partners available at axis.com/vms |

AXIS T8312 Video Surveillance Keypad

| Functionality | |
|---------------------------|--|
| | 22 keys with customizable function |
| | Weight: 630 g (1.4 lb) |
| General | |
| Connectors | 2 x USB Type A, 1 x USB Type B |
| Dimensions | Height: 35 mm (1.4 in) Width: 182 mm (7.2 in) Depth: 181 mm (7.1 in) |
| Included accessories | 1 x USB cable 40 cm (15.7 in) for connecting units, 1 x USB cable 200 cm (78.7 in) for connecting to PC, Installation Guide |
| Video management software | AXIS Camera Station version 5.17 or higher, video management software from Axis Application Development Partners available at axis.com/vms |

AXIS T8313 Video Surveillance Jog Dial

| Functionality | |
|---------------------------|--|
| | 6 hotkeys with customizable function Shuttle operating angle 160° |
| | Weight: 630 g (1.4 lb) |
| General | |
| Connectors | USB Type B |
| Dimensions | Height: 45 mm (1.8 in) Width: 182 mm (7.2 in) Depth: 181 mm (7.1 in) |
| Included accessories | 1 x USB cable 40 cm (15.7 in), 1 x USB cable 80 cm (78.7 in) for connections between units, Installation Guide |
| Video management software | AXIS Camera Station version 5.17 or higher, video management software from Axis Application Development Partners available at axis.com/vms |

Environmental responsibility:

axis.com/environmental-responsibility