



2-port PCIe Gen3 x8 expansion card

| | |
|----------------------------|---|
| Connector | 2 Channels (1 x 2 SFF-8644 connectors) |
| PCIe and Lanes | PCIe Gen3 x8 |
| Transmission Rates | Max. 64Gbps |
| Bracket | Low-profile (default). Low-profile flat and Full-height brackets are also included. |
| Dimensions (L x W x H) | 112.65 × 68.9 × 18.26 mm |
| Supported Cable | CAB-PCIE10M-8644-4X, CAB-PCIE10M-8644-8X |
| Standard Warranty | 3 years |
| Operating Temperature | 0 - 40 °C (32°F - 104°F) |
| Storage temperature | -20 - 70°C (-4°F - 158°F) |
| Relative humidity | 5-95% RH non-condensing, wet bulb: 27°C (80.6°F) |
| JBOD supported | TL-R1200PES-RP, TL-R1600PES-RP, TL-R2400PES-RP |
| Supported Operating System | QuTS hero 5.1.2 or later; QTS 5.1.2 or later |
| Note [NAS] | <u>Recommended models (please update your NAS OS and BIOS to the latest version).</u> |

Note: QNAP reserves the right to replace partial parts or accessories if the original is no longer available from its manufacturer/supplier. Any replacement would be fully tested and verified to meet strict compatibility and stability guidelines and will deliver identical performance to the original.

Product images are for illustrative purposes only and may differ from the actual product. Due to differences in monitors, colors of products may also appear different to those shown on the site.

Designs and specifications are subject to change without notice.